



JPH1500 Hydraulic Outboard Jack Plate

Ideal for bass boats, bay boats, flats boats, and performance skiffs

Technical Specifications

Engine Compatibility

- Rated for: 10–150 HP outboards
- Standard outboard bolt pattern

Hydraulic System

- 12V hydraulic actuator
- Smooth, controlled vertical travel
- Relay wiring harness included
- Rocker switch included
- Voltage requirement: 10.5–14V

Construction & Materials

- High-strength aluminum alloy
- Corrosion-resistant finish
- Integrated anode pocket
- Size: 2.45" × 0.98"
- Hole spec: 1/4"-28 UNF
- Depth: 0.55"
- Stainless hardware (engine-manufacturer approved)



Mounting Requirements

- Use 4–6 bolts depending on engine HP and setback
- For 60+ HP or 10"+ setback: 6 bolts recommended
- Engine-side bolt spec: M10×35 GB bolts
- Torque values: Follow engine manufacturer recommendations

Clearance & Safety

- Full steering travel must be verified at all trim positions
- Provides 2.5" lift offset at lowest position
- Zero-flex vertical bracket design

Maintenance

- Inspect every 100 hours or 6 months
- Fresh-water rinse after each use
- Integrated grease-fitting lubrication system

Warranty

- 2-Year extended warranty covers all defects of materials and workmanship